

Importers and Distributors of CCTV products

NVR1008POE

8 Channel 1080P Network Video Recorder with built-in POE



▶ FEATURES

- Can connect IP camera, IP speed dome camera and DVS;
- Support Onvif protocol;
- Support megapixel HD network video preview, storage and playback;
- Click any area and zoom in or zoom out on the image by mouse;
- Support digital zooming under preview and playback modes;
- Support search, playback and backup by event;
- Support 4ch playback simultaneously

Rear Panel



	Operating System	Embedded LINUX operating system
	Image Code Control	Image code quality adjustable, variable
	Dual Stream	Each channel can set main stream and sub stream
	Video Standard	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30f
	Monitoring Image	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
	Image Motion Detection	Each screen can set mutiple detection areas and set 6-level
	Recording Playback Quality	4ch 720P playback in 8ch 720P mode;1ch 1080P playback in 8ch
	Region Cover	Every channel can set 4 cover regions (IPC Support)
	Recording Mode	Support manual , auto, dynamic detection, alarm trigger
	Backup	Support USB disk, USB mobile HDD, USB DVD-RW and network
	Operation	Mouse
	Local Login	Username and password
	Recording	Local HDD, network
Video & Audio output	Video Output	1 Ch. VGA, 1 Ch. HDMI
	Audio Output	1 Ch. RCA connector
Video	Video Compression	H.264 main profile
	Video Input	8 ch
	Video Input Port	RJ45
	Monitoring Resolution	1280x720
	Compression	1280x720/640x360
	Video Frame Rate	Preview:30fps/ch, Compression :1 - 20fps/ch
	Video Output Rate	32kbps - 8000kbps
	Audio Compression Format	G.729
Audio	Audio Input	4ch network input
HDD	HDD Port	1 SATA HDD port
	Max Capacity	Each port supports max. 4TB HDD
External Ports	USB Port	3 USB 2.0
	Network Port	1 RJ45 Gigabit Ethernet network interface
	Alarm Input/Output	2ch alarm input, 1ch alarm output
	Serial Interface	1 RS - 485
Other	Power Supply	12 2.6A
	Power Consumption	≤25W (excluding hard disk)
	Working Temperature	- 10°C—55°C
	Working Humidity	10%—90%
	Dimensions	350mm x 240mm x 70mm
	Weight	1.7Kg