

Importers and Distributors of CCTV products

DVR08TVI-N



8CH HD CCTV DVR

FEATURES

Free P2P Cloud EaZy Networking*

- ❖ Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- ❖ The “Buddy” feature to share the device access permission to other people.
- ❖ Device login / out notifications reported.



Push Status -

Active Event Notification with EagleEyes App

- ❖ Push Status to send instant notifications for system events, such as video loss or HDD data removal.



Video Backup

- ❖ Regular backup could be configured to automatically copy video footages to the specified location (USB drive or FTP) at the specified time.

Remote Surveillance

- ❖ Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- ❖ CMS Lite for 24 devices central management
- ❖ Applicable also to Apple’s media player, QuickTime.

Independent Channel Control

- ❖ Definable “Resolution” / “Quality” / “IPS” by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

- ❖ Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

SPECIFICATIONS

| ▼ Video | |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video System | NTSC / PAL (auto detection) |
| Video Compression Format | H.264 |
| Video Input | 8 channels (Composite video signal 1 Vp-p 75Ω BNC) |
| Video Output | VGA HDMI |
| | YES YES |
| ▼ Record & Backup | |
| Maximum Recording Rate | 1080P 720P QHD Frame Field CIF |
| | 1920 x 1080 pixels with 120 IPS 1280 x 720 pixels with 240 IPS 960 x 540 pixels with 240 IPS 704×480 pixels with 240 IPS <NTSC> / 704×576 pixels with 200 IPS <PAL> 704 x 240 pixels with 240 IPS <NTSC> / 704×288 pixels with 200 IPS <PAL> 352×240 pixels with 240 IPS <NTSC> / 352×288 pixels with 200 IPS <PAL> |
| Recording Mode | Manual / Timer / Motion / Alarm / Remote |
| Pre-alarm Recording | YES |
| Playback Channel | 8CH |
| Quick Search | Time / Motion / Alarm search mode |
| Backup Device | USB 2.0 flash drive / Network |
| Regular Backup | YES |
| ▼ Audio | |
| Audio Input | 1 audio input |
| Audio Output | 1 Audio output (Mono) |
| ▼ General | |
| Hard Disk Storage** | 1 SATA HDD |
| SATA Interface | YES |
| Image Quality Setting | SUPER BEST / BEST / HIGH / NORMAL |
| USB Mouse Control | YES |
| Motion Detection Area | 16 × 12 grids per channel |
| Motion Detection Sensitivity | 3 adjustable parameters for accurate detection |
| Event Notification | Push Status / FTP / E-Mail |
| Picture Zoom | 2X digital zoom |
| PTZ Control | YES |
| Alarm I/O | 1 input, 1 output |
| Key Lock (Password Protection) | YES |
| User Level | 4 user levels for different access privilege |
| Video Loss Detection | YES |
| Camera Title | Supports up to 25 letters |
| Video Adjustable | Hue / Saturation / Contrast / Brightness |
| Date Display Format | YY/MM/DD, DD/MM/YY & MM/DD/YY |
| Daylight Saving | YES |
| Power Source (±10%) | DC12V / 2A |
| Operating Temperature | 10°C ~ 40°C (50°F ~ 104°F) |
| Operating Humidity | 10% ~ 85% |
| Dimensions (mm)*** | 345(W)×58.8(H)×223(D) |
| Net weight | 2 Kg |
| ▼ Network | |
| Ethernet | 10/100 Base-T. Supports remote control and live view via Ethernet |
| Network Protocol | TCP/IP, PPPOE, DHCP and DDNS |

▶ SPECIFICATIONS

| ▼ Remote Surveillance from PC | | |
|-------------------------------------|----------------------------------------------------------------|-------------------------------------------------|
| Compatible Operating System | Windows & MAC | |
| Compatible Program | Web Browser: | Internet Explorer, Google Chrome & Safari |
| | CMS Lite: | 24CH central management software for Windows OS |
| | QuickTime: | For both Windows and MAC operating systems |
| Max. online users | 20 | |
| Web Transmitting Compression Format | H.264 | |
| Network Live Audio | YES | |
| Remote Independent Operation | YES | |
| Remote Event Download & Playback | YES | |
| ▼ Mobile Surveillance | | |
| App | EagleEyes | |
| Compatible Devices | iOS & Android devices | |
| Push Status | YES | |
| ▼ Others | | |
| EaZy Networking | YES | |
| DCCS Support | YES | |
| AVTECH Free DDNS service | YES | |
| Multiplex Operation | Live display / record / playback / backup / network operations | |
| System Recovery | System auto recovery after power failure | |
| Optional Peripherals | HDMI Matrix (HDM02) | |

* The specifications are subject to change without notice.

** 1 HDD capacity up to 6TB

*** Dimensional tolerance: ±5mm

▶ REAR PANEL

